

FORM RELEASE



FORM TREATMENT

Neutral

Liner Kote

DESCRIPTION: Is a chemically neutral release agent in a mineral oil carrier. It is water insoluble, low sulphur and contains no waxes. Improves release of form liner from concrete. Reduces concrete buildup on form liner and formwork. Provides conditioning of urethane elastomer form liner. Finished concrete surface is free from residue, stain or discoloration.

APPLICATION: Provides a high carbon content on the form surface that is resistant to concrete adhesion. Spray application is recommended with spray cans or power sprayers. The spraying angle must be varied to ensure proper Coverage of all form liner pattern features.

COVERAGE:
Rate is approximately 500 ft²/gal. depending on the form liner material and pattern texture.

No.	Size
SY 5GLK	5 gal. pail, 50 lbs.

Magic Kote

DESCRIPTION: Magic Kote is a chemically neutral release agent in a petroleum oil carrier. It is water insoluble, low sulphur and contains no waxes. Improves release of formwork from concrete. Reduces concrete buildup on formwork. Reduces cleaning of formwork.

APPLICATION: Provides a high carbon content on the form surface that is resistant to concrete adhesion. Spray application is recommended, with spray cans or power sprayers. But brush, roller or flooding techniques may be used as alternative application methods.

COVERAGE:
Alum. Plastic, Fiberglass
2,000 ft²/gal.

Medium Density Plywood
1,500 ft²/gal.

BB Grade Plyform
1,200 ft²/gal.

Dimensional lumber
1,000 ft²/gal.

No.	Size
SY 5GMK	5 gal. pail, 50 lbs., 36/pallet
SY 55GMK	55 gal. drum, 550 lbs.