

FLASHING



MASONRY

Blueskin®

Blueskin®, when applied appropriately, will virtually eliminate drafts and water leaks at critical areas around the exterior of your building. The membrane is made of an SBS rubberized asphalt compound that is integrally laminated to a (blue) cross laminated polyethylene film, and is specially designed to be self-adhered to all prepared substrates of concrete, CMU's, primed steel, rigid vinyl, mill finish and anodized aluminum, galvanized metal, drywall, plywood, and OSB sheathing. The SBS membrane is flexible with excellent adhesion at low temperatures. Blueskin® is impermeable to air, moisture vapor, and water; and is self-sealing when penetrated with most fasteners. Stocked in 40 mil thickness.



No.	Size	Wt (lbs)
CD BS640	6'x75'	9.5
CD BS940	9'x75'	14.3
CD BS1240	12'x75'	18.0
CD BS1840	18'x75'	27.0
CD BS3640	36'x75'	54.0
CD SBP	5 gal. Primer	35.0
CD BSCAULK	29 fl. oz. Caulk	3.0

Permabarrier


A composite, self adhesive sheet type waterproofing membrane consisting of 8 mils of high density cross laminated polyethylene bonded to 32 mils of rubberized asphalt for a total thickness of 40 mils. It is self sealing, and excellent puncture resistance. It is self healing since the adhesive system will elongate and recover if somewhat damaged. Needs no reglet when adhering membrane to vertical substrate. Applications include; thru wall flashing; concealed flashing; foundation sill flashing; base flashing; spandrel flashing; head and sill flashing and papapet flashing. A primer is necessary for dusty and certain substrates. Consult technical bulletin for more information.



No.	Size	Wt (lbs)	Qty/Ctn (lbs)
WR 12PB	12'x75'	25.0	3
WR 18PB	12'x75'	38.0	2
WR 36PB	12'x75'	75.0	1
Accessories:			
WR 5GVOCP	5 gal. pail primer	50.0	
H TEM3000	30 fl. oz. cartridge	2.70	12

Drip Edge Flashing

Drip Edge Flashing, when used with thru wall flashing material creates an effective moisture barrier. The partially embedded drip edge produces an aesthetic finish. Fabricated from 26 gauge stainless steel. 10 lf lengths.



No.	Wt/Pc (lbs)
DA DE	3.0